



Push trolley

Produktinformation

Push trolley for IPE and T beams. The wheels are equipped with duration lubricated ball bearings. The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

Märkning: Enligt standard, CE-märkning

Standard: EN 13157

Säkerhetsfaktor: 4:1

Art.nr	Max last (WLL) ton	Beam width mm	Min. kurvradie mm	B,	D mm	E,	F,	G,	H,	J,	K mm	L	M mm	Vikt kg	Ca. levtid (arbetsdagar)
SIVA05H	0,5	55-220	500	285	3	40	12,5	25	80	198	158	55	28	5	1
SIVA05HL	0,5	55-305	500	385	3	40	12,5	25	80	198	158	55	28	5,4	1
SIVA10H	1	58-220	700	300	3	31	17	29	96	238	183	68	37	8,8	1
SIVA10HL	1	58-305	700	238	3	31	17	29	96	-	183	68	37	9,3	1
SIVA20H	2	66-220	900	300	3	31	20	36	110	277	208	80	48	14	1
SIVA20HL	2	66-305	900	405	3	31	20	36	110	277	208	80	48	14,8	1
SIVA30H	3	74-220	1 200	328	3	31	26	46	132	324	249	100	56	23	1
SIVA30HL	3	74-305	1 200	429	~3	31	26	46	132	324	249	100	56	24,1	1
SIVA50H	5	90-220	1 000	354	5	40	28	52	155	373	296,5	120	65	40	1
SIVA50HL	5	90-305	1 000	435	~5	40	28	52	155	373	296,5	120	65	41,1	1

Ritning & mått

