



Eye self-locking hook with ball bearing swivel, grade 80

Produktinformation

The hook locks automatically when lifting starts and rotates easily also with full load.

Märkning: Enligt standard, CE-märkning

Standard: EN 1677-3

Säkerhetsfaktor: 4:1

Klass: 8

Art.nr	Max last (WLL) ton	Till kätting Ø mm	A mm	B, C, mm	L1 mm	L	T mm	E, mm	M mm	N mm	Ø mm	Vikt kg	Ca. levtid (arbetsdagar)
VAKL6KL	1,12	6	32	11 34	160	194	28	32	70	15	34	0,71	1
VAKL78KL	2	7-8	36	13 40	202	240	35	39	88	20	44	1,1	1
VAKL10KL	3,15	10	42	16 48	237	283	45	48	108	26	58	2	1
VAKL13KL	5,3	13	50	17 58	282	343	52	65	134	33	70	4	1
VAKL16KL	8	16	61	22 60	342	419	63	65	169	38	86	7,3	1
VAKL20KL	12,5	20	76	27 75	400	483	86	85	186	50	97	11,6	1
VAKL22KL	15	22	97	33 97	466	564	76	80	202	52	98	16	1
VAKL26KL	21,2	26	123	42 115	544	661	96	125	244	60	110	21,5	1

Ritning & mått

