



Concrete lifting buckets with rubber hose

Produktinformation

The octagonal concrete bucket with lever opening and rubber hose, model BCE, is the ideal choice for precise and reliable pouring in the most demanding construction sites with intensive use. Its design, targeted to meet the needs of the most challenging construction sites, makes it indispensable for accurately pouring large quantities of concrete into formwork, pillars, or slabs, avoiding potential structural problems caused by pouring errors. The bucket is equipped with a guillotine valve operated by a lever. The presence of a spring allows for automatic closure of the discharge, while the rope enables managing and partially opening the bucket valve even at height. The two-meter-long rubber hose, with a diameter of 200 mm, ensures a controlled and precise flow of concrete during the pour.

Other models are also available. Please ask our sales department for more information.

Märkning: CE-märkning

| Art.nr | Max last (WLL) ton | Volume liter | A mm | B, mm | C, mm | D mm | Vikt kg | Ca. levtid (arbetsdagar) |
|---------------|-----------------------|-----------------|---------|----------|----------|---------|------------|--------------------------|
| BETNOS500SUK | 1,3 | 500 | 2 387 | 1 128 | 1 000 | 1 505 | 225 | 56 |
| BETNOS1000SUK | 2,6 | 1 000 | 2 807 | 1 447 | 1 200 | 1 712 | 340 | 56 |
| BETNOS1500SUK | 3,9 | 1 500 | 3 048 | 1 647 | 1 300 | 1 925 | 420 | 56 |
| BETNOS2500SUK | 6,5 | 2 500 | 2 008 | 1 780 | 1 780 | 1 927 | 546 | 56 |

Ritning & mått

