



Lifting eye screw with swivel, grade 80

Produktinformation

Lifting screw with swivel for all lifting directions. Also available with longer 120 mm thread.

Märkning: Enligt standard, CE-märkning

Standard: EN 1677-1

Säkerhetsfaktor: 4:1

Art.nr	Max last (WLL) ton	Gänga mm	Eye diameter mm	diameter eye inside mm	Thread pitch mm	b mm	g mm	t mm	e mm	d mm	Vikt kg	Ca. levtid (arbetsdagar)
NS8KL1003	0,45	M10	14	55x30	1,5	36	51	41	18	M10	0,43	1
NS8KL1205	0,5	M12	14	55x30	1,75	36	51	41	18	M12	0,44	1
NS8KL161	1,1	M16	14	55x30	2	36	52	42	20	M16	0,46	1
NS8KL161120	1,1	M16	14	55x30	2	36	52	42	120	M16	0,46	1
NS8KL202	2	M20	16	70x34	2,5	50	68	56	30	M20	0,96	1
NS8KL202120	2	M20	16	70x34	2,5	50	68	56	120	M20	0,96	1
NS8KL243120	3,2	M24	18	85x37	3	57	78	65,5	120	M24	1,45	1
NS8KL2432	3,2	M24	18	85x37	3	57	78	65,5	40	M24	1,45	1
NS8KL305120	5,3	M30	20	85x37	3,5	66	97	80,5	120	M30	2,17	1
NS8KL3053	5,3	M30	20	85x37	3,5	66	97	80,5	35	M30	2,17	1
NS8KL308	8	M30	22	115x50	3,5	80	112	92	35	M30	3,57	1
NS8KL308120	8	M30	22	115x50	3,5	80	112	92	120	M30	3,57	1
NS8KL368	8	M36	22	115x50	4	80	109	89,5	50	M36	4,17	14
NS8KL368120	8	M36	22	115x50	4	80	109	89,5	120	M36	4,17	1
NS8KL4210	10	M42	25	115x50	4,5	80	109	89,5	50	M42	3,67	1
NS8KL4810	10	M48	25	115x50	5	80	109	89,5	50	M48	4,02	14
NS8KL4510	10	M45	25	115x50	4,5	80	109	89,5	60	M45	4,17	1
NS8KL5615	15	M56	32	152x70	5,5	117	310	280	84	M56	11,6	1
NS8KL6415	15	M64	32	152x70	6	117	310	280	95	M64	12,6	1

Ritning & mått

