



## Lifting eye nuts DIN 582

### Produktinformation

Lifting eye nuts for vertical lifting

**Märkning:** Enligt standard, CE-märkning

**Standard:** DIN 582

**Säkerhetsfaktor:** 4:1

Art.nr	Max last (WLL) ton	Gänga mm	Förpackning	Thread pitch mm	d1 mm	d2 mm	d3 mm	d4 mm	h mm	k mm	Vikt kg	Ca. levtid (arbetsdagar)
NSM06	0,06	M6	50	1	M6	20	36	20	18	8	0,045	1
NSM08	0,14	M8	50	1,25	M8	20	36	20	18	8	0,05	1
NSM10	0,23	M10	50	1,5	M10	25	45	25	22,5	10	0,09	1
NSM12	0,34	M12	25	1,75	M12	30	54	30	26	12	0,16	1
NSM14	0,34	M14	25	2	M14	35	63	35	30,5	14	0,24	1
NSM16	0,7	M16	10	2	M16	35	63	35	30,5	14	0,24	1
NSM18	0,85	M18	10	2,5	M18	40	72	40	35	16	0,36	14
NSM20	1,2	M20	10	2,5	M20	40	72	40	35	16	0,36	1
NSM22	1,2	M22	1	2,5	M22	45	81	45	40	18	0,58	1
NSM24	1,8	M24	1	3	M24	50	90	50	45	20	0,72	1
NSM27	2,1	M27	1	3	M27	50	90	50	45	20	0,7	1
NSM33	3,2	M33	1	3,5	M33	65	108	60	55	24	1,3	1
NSM30	3,2	M30	1	3,5	M30	65	108	60	55	24	1,32	1
NSM39	4,6	M39	1	4	M39	75	126	70	65	28	2,02	14
NSM36	4,6	M36	1	4	M36	75	126	70	65	28	2,08	1
NSM45	6,3	M45	1	4,5	M45	85	144	80	75	32	3,04	14
NSM42	6,3	M42	1	4,5	M42	85	144	80	75	32	3,11	1
NSM52	8,6	M52	1	5	M52	100	166	90	85	38	4,95	14
NSM48	8,6	M48	1	5	M48	100	166	90	85	38	5,02	1
NSM56	11,5	M56	1	5,5	M56	110	184	100	95	42	6,69	1
NSM64	16	M64	1	6	M64	120	206	110	105	48	9,3	1

## Ritning & mått

