



Lifting eye screw DIN 580

Produktinformation

Lifting eye screws for vertical lifting

Märkning: Enligt standard, CE-märkning

Standard: DIN 580

Säkerhetsfaktor: 4:1

Art.nr	Max last (WLL) ton	Gänga mm	Förpackning	Thread pitch mm	d1 mm	d2 mm	d3 mm	d4 mm	h mm	k mm	l mm	Vikt kg	Ca. levtid (arbetsdagar)
NSR06	0,08	M6	50	1	M6	20	36	20	18	8	13	0,045	1
NSR08	0,14	M8	50	1,25	M8	20	36	20	18	8	13	0,05	1
NSR10	0,23	M10	50	1,5	M10	25	45	25	22,5	10	17	0,09	1
NSR12	0,34	M12	25	1,75	M12	30	54	30	26	12	20,5	0,16	1
NSR14	0,34	M14	25	2	M14	35	63	35	30,5	14	27	0,24	1
NSR16	0,7	M16	10	2	M16	35	63	35	30,5	14	27	0,24	1
NSR18	0,85	M18	10	2,5	M18	40	72	40	35	16	30	0,36	1
NSR20	1,2	M20	10	2,5	M20	40	72	40	35	16	30	0,36	1
NSR22	1,2	M22	1	2,5	M22	45	81	45	40	18	35	0,58	1
NSR24	1,8	M24	1	3	M24	50	90	50	45	20	36	0,72	1
NSR27	2,1	M27	1	3	M27	50	90	50	45	20	36	0,7	1
NSR33	3,2	M33	1	3,5	M33	65	108	60	55	24	45	1,3	14
NSR30	3,2	M30	1	3,5	M30	65	108	60	55	24	45	1,32	1
NSR39	4,6	M39	1	4	M39	75	126	70	65	28	54	2,02	14
NSR36	4,6	M36	1	4	M36	75	126	70	65	28	54	2,08	1
NSR45	6,3	M45	1	4,5	M45	85	144	80	75	32	63	3,04	14
NSR42	6,3	M42	1	4,5	M42	85	144	80	75	32	63	3,11	1
NSR52	8,6	M52	1	5	M52	100	166	90	85	38	68	4,95	14
NSR48	8,6	M48	1	5	M48	100	166	90	85	38	68	5,02	1
NSR56	11,5	M56	1	5,5	M56	110	184	100	95	42	78	6,69	1
NSR64	16	M64	1	6	M64	120	206	110	105	48	90	9,3	14

Ritning & mått

