



Shackles, SAE - bow model

Produktinformation

Shackles approved for lifting. Bow shackles are suitable for use when more than one attachment is to be made to the body (multi-leg systems), or to allow freedom of movement in the plane of the bow. Screw pin shackles are easily manipulated. They are typically suitable for non-permanent applications and one-off installations, when there is no tendency for the pin to unscrew and the shackle can be observed under operation.

Märkning: Enligt standard, CE-märkning

Standard: US. FED. SPEC. RR-C-271F

Säkerhetsfaktor: 6:1

Art.nr	Max last (WLL) ton	Storlek tum	Amm mm	B mm	C mm	Dmm mm	E mm	F mm	G, mm	H, mm	Imm mm	Mmm mm	Nmm mm	Vikt kg	Ca. levtid (arbetsdagar)
SAK03PBP	0,33	3/16	10	7	22	5	15	14	25	38	4	29	5	0,03	1
SAK05PBP	0,5	1/4	12	8	29	7	20	16	33	47	5	35	5	0,05	1
SAK07PBP	0,75	5/16	14	10	31	8	22	19	38	53	6	42	8	0,09	1
SAK10PBP	1	3/8	17	11	37	10	26	23	45	63	7	52	10	0,14	1
SAK15PBP	1,5	7/16	19	13	43	11	30	27	52	74	8	61	11	0,17	1
SAK20PBP	2	1/2	21	16	48	13	34	30	59	84	10	69	13	0,33	1
SAK32PBP	3,25	5/8	27	19	61	16	43	38	75	106	11	85	18	0,62	1
SAK47PBP	4,75	3/4	32	23	72	19	51	46	89	126	13	101	21	1,07	1
SAK65PBP	6,5	7/8	37	26	84	23	58	53	102	148	13	114	25	1,64	1
SAK85PBP	8,5	1	43	29	96	26	69	61	119	167	14	129	27	2,28	1
SAK95PBP	9,5	1-1/8	46	32	108	30	74	69	131	190	16	142	32	3,36	1
SAK120PBP	12	1-1/4	52	35	119	33	93	76	146	210	18	156	35	4,31	1
SAK135PBP	13,5	1-3/8	57	38	133	36	92	84	162	233	19	174	38	6,14	1
SAK170PBP	17	1-1/2	61	42	146	39	99	92	175	254	21	187	41	7,8	1
SAK250PBP	25	1-3/4	73	51	178	47	127	106	225	313	26	231	57	12,6	1
SAK350PBP	35	2	83	57	197	53	146	122	253	348	31	263	61	20,4	1
SAK550PBP	55	2-1/2	105	70	267	69	184	145	327	453	35	330	80	38,9	1
SAK850PBP	85	3	127	82	330	76	200	165	367	546	38	490	105	70	1

Ritning & mått

