

Shackles, SAE - dee mode with locking

Produktinformation



Shackles approved for lifting. Dee shackles are suitable for use when two pieces of lifting equipment / an installment are joined together (one-leg systems). Locking bolt shackles are recommended for long-term and permanent installations, or when there is a natural tendency for the pin to unscrew (rotate) in the application, or when the shackle cannot be observed under operation.


... [Read more](#)

Märkning: Enligt standard, CE-märkning
Standard: US. FED. SPEC. RR-C-271F

Säkerhetsfaktor: 6:1

Shackles, SAE - dee mode with locking

Ritning & mått



Mer information / Reservdelar

Art.nr	Max last (WLL) ton	Storlek tum	A mm	B mm	C mm	D mm	F mm	G mm	H mm	M mm	N mm	Vikt kg
SAK05SLBP	0,5	1/4	12	8	19	7	16	25	41	40	7	0,06
SAK07SLBP	0,75	5/16	14	10	26	8	19	30	49	46	8	0,1
SAK10SLBP	1	3/8	17	11	31	10	23	36	59	55	10	0,15
SAK15SLBP	1,5	7/16	19	13	36	11	27	41	68	64	11	0,22
SAK20SLBP	2	1/2	21	16	42	13	30	46	77	71	13	0,34
SAK32SLBP	3,25	5/8	27	19	51	16	38	59	96	90	16	0,67
SAK47SLBP	4,75	3/4	32	23	61	19	46	70	115	103	21	1,14
SAK65SLBP	6,5	7/8	37	26	72	23	53	81	135	120	25	1,74
SAK85SLBP	8,5	1	43	29	81	26	61	94	151	135	26	2,52
SAK95SLBP	9,5	1-1/8	46	32	91	29	69	103	172	150	32	3,45
SAK120SLBP	12	1-1/4	52	35	100	32	76	115	191	165	35	4,9
SAK135SLBP	13,5	1-3/8	57	38	111	35	84	127	210	183	38	6,24
SAK170SLBP	17	1-1/2	61	42	122	38	92	137	230	196	42	8,39
SAK250SLBP	25	1-3/4	73	51	146	45	106	162	279	230	54	14,2
SAK350SLBP	35	2	82	57	172	51	122	184	312	264	51	21,2
SAK550SLBP	55	2-1/2	105	70	203	67	145	238	377	344	67	38,6
SAK850SLBP	85	3	127	83	216	76	165	279	429	419	89	56
SAK1200SLBP	120	3-1/2	133	96	240	92	203	320	500	510	102	95