



Shackles, SAE - dee model

Produktinformation

Shackles approved for lifting. Dee shackles are suitable for use when two pieces of lifting equipment / an installment are joined together (one-leg systems). Screw pin shackles are easily manipulated. They are typically suitable for non-permanent applications and one-off installations, when there is no tendency for the pin to unscrew and the shackle can be observed under operation.

Märkning: Enligt standard, CE-märkning

Standard: US. FED. SPEC. RR-C-271F

Säkerhetsfaktor: 6:1

Art.nr	Max last (WLL) ton	Storlek tum	Amm mm	B mm	C mm	Dmm mm	F mm	G, mm	H, mm	Imm mm	Mmm mm	Vikt kg	Ca. levtid (arbetsdagar)
SAK03SBP	0,33	3/16	10	7	16	5	14	20	31	4	29	0,02	1
SAK05SBP	0,5	1/4	12	8	23	7	16	25	41	5	35	0,05	1
SAK07SBP	0,75	5/16	14	10	26	8	19	30	49	6	42	0,08	1
SAK10SBP	1	3/8	17	11	32	10	23	36	59	7	52	0,13	1
SAK15SBP	1,5	7/16	19	13	37	11	27	42	68	8	61	0,2	1
SAK20SBP	2	1/2	21	16	42	13	30	46	77	10	69	0,27	1
SAK32SBP	3,25	5/8	27	19	51	16	37	59	96	11	85	0,57	1
SAK47SBP	4,75	3/4	32	23	61	19	46	70	115	13	101	1,2	1
SAK65SBP	6,5	7/8	37	26	72	23	53	81	135	13	114	1,43	1
SAK85SBP	8,5	1	43	29	81	25	61	94	151	14	129	2,15	1
SAK95SBP	9,5	1-1/8	46	32	91	29	69	103	172	16	142	3,06	1
SAK120SBP	12	1-1/4	52	35	100	32	76	115	191	18	156	4,11	1
SAK135SBP	13,5	1-3/8	57	38	111	35	84	127	210	19	174	5,28	1
SAK170SBP	17	1-1/2	61	42	122	38	92	137	230	21	187	7,23	1
SAK250SBP	25	1-3/4	73	51	146	45	106	162	279	26	231	12,1	1
SAK350SBP	35	2	83	57	172	51	122	184	312	31	263	19,2	1
SAK550SBP	55	2-1/2	105	70	203	67	145	238	377	35	330	32,5	1

Ritning & mått

