

## Stållina 18x7-WSC rotationsfattig

### Produktinformation



**ISO 4309 Rope Category No:** Alla dimensioner RCN.23-1

**Konstruktion:** Rotationsfattig, 18x7-WSC (133-trådig)


**Märkning:** Enligt standard

**Standard:** EN 12385-4

**Fyllnadsfaktor:** 0.55

**RCN:** 23-1

Telfer/ Travers



<b>Art.nr</b>	<b>Lindiameter mm</b>	<b>Trådållfasthet N/mm<sup>2</sup></b>	<b>Ytbehandling</b>	<b>Rope lay</b>	<b>Min brottkraft kN</b>	<b>Stålarea mm<sup>2</sup></b>	<b>Smörjning</b>	<b>Vikt kg/100m</b>
TEKK04	4	1 960	Galvaniserad	sZ	10,3	6,9	A-1	6,4
TEKK05	5	1 960	Galvaniserad	sZ	16,1	10,8	A-1	10
TEKK06	6	1 960	Galvaniserad	sZ	23,1	15,6	A-1	14
TEKK07	7	1 960	Galvaniserad	sZ	31,5	21,2	A-1	20
TEKK08	8	1 960	Galvaniserad	sZ	41,1	27,7	A-1	26