

Lift graded turnbuckles with closed body

Produktinformation

Lift graded turnbuckle for professional use. Equipped with locking nuts and fork/fork ends.

Märkning: CE-märkning

Säkerhetsfaktor: 5:1



Art.nr	Max last (WLL) ton	Gänga	A mm	B, mm	C, mm	D mm	E, mm	G, mm	d mm	h mm	L1 mm	L min. mm	L max. mm	Vikt kg	Ca. levtid (arbetsdagar)
VRH06	0,2	M6	19	7	16	14,5	100	12	M5	6,5	54	180	255	0,13	1
VRH08	0,32	M8	23	9	22	17,2	108	14	M6	8,5	59	210	285	0,25	1
VRH10	0,5	M10	26	10	21	17,2	150	17	M8	7	79	250	360	0,3	1
VRH12	0,7	M12	33	13	26	21,3	195	22	M10	8	106	330	480	0,65	1
VRH16	1,2	M16	42	18	32	27	230	26	M12	8	122	395	580	1,25	1
VRH19	1,5	M20	50	20	38	34	270	32	M16	12	145	460	680	2,2	1
VRH22	2,2	M22	44	25	50	34	295	46	M20	12	160	500	720	3,3	1
VRH25	3,2	M24	51	28	54	42	325	52	M22	12	175	555	800	4,6	1
VRH32	4,8	M33	62	38	71,5	50	370	60	M27	12	220	700	970	8,5	1
VRH38	6	M39	79	45	83,5	60,3	400	75	M33	16	230	780	1 060	15	1
VRH45	8,5	M45	94	50	86	76	400	85	M39	16	235	800	1 050	21	1
VRH50	11	M52	98	58	97,5	76	400	92	M45	16	240	825	1 050	24	1

Ritning & mått

