

Electric-hydraulic lifting tables 400V

Produktinformation




For installation, repairs, packaging etc. Operating voltage 3-phase /380-400 V/50 Hz. Control device (cable) with lifting and lowering functions, as well as emergency stop. Equipped with a protection frame, which prevents the table from lowering, if something gets in between the plates. Electromagnetic valve, the table can not be lowered (it will stop), if a hose breaks. Delivered completely assembled without plug ... [Read more](#)

Märkning: Enligt standard, CE-märkning

Standard: EN 1570

Electric-hydraulic lifting tables 400V

Ritning & mått



Lyfttabell

Art.nr	Table measures mm	Lifting times	Max load kg	Min höjd mm	Höjd mm	L mm	B mm	L1 mm	B1 mm	H mm	Vikt kg
NOSP1000H	1300 x 820	20-25	1 000	205	990	1 300	820	1 266	680	205 - 990	164
NOSP1000HL	1300 x 1000	20-25	1 000	205	990	1 300	1 000	1 266	680	205-990	190
NOSP2000H	1600 x 1000	16-22	2 000	230	1 000	1 600	1 000	1 255	785	230 - 1000	270
NOSP4000H	2000 x 1200	30-40	4 000	240	1 050	2 000	1 200	1 600	930	240 - 1050	446