

Anti-slip mats

Produktinformation



Available in rolls or pieces. Protective anti-slip mat for transported goods. Its high coefficient of sliding friction - documented in testing according to VDI 2700 Sheet 14 (Draft) – provides outstanding anti-slip performance. Utilized widely in commercial transport applications, mats are also used successfully as intermediate layer pads in the packaging industry.

Recycled rubber crumbs bonded with Polyurethane.

Anti-slip mats are generally usable several times before they need to be replaced due to discard criteria.

- Fire resistance: Efl (B2) (EN 13501-1)
- Coefficient of Sliding friction: min. $\mu = 0.8$
- Elongation at break: min. 60% (DIN EN ISO 1798)
- Contact surfaces: wooden pallet, anti-slip textured lorry flooring (VDI 2700 Sheet 14)
- Pressure behavior: no plastic deformation after 24 hours strain. Ballast: grid box 1000 kg (VDI 2700 Sheet 15)
- Resistance: conditionally resistant to acids and bases
- UV-Resistance: resistant to DIN EN 1297 and DIN EN ISO 3386-2

Märkning: Enligt standard

Standard: EN 12195-2

Art.nr	Längd m	Storlek mm	Tjocklek mm	Trådhållfasthet N/mm ²	Antal/förp.	Loading strength t/m ²	Vikt kg/m ²	Ca. levtid (arbetsdagar)
KITMA5250	-	250 x 250	5	0,6	20	180	-	1
KITMA3R	20	1 250	3	0,6	-	180	3	1
KITMA3R300	20	300	3	0,6	-	180	3	1
KITMA5R	12	1 250	5	0,6	-	180	5	1
KITMA6R	10	1 250	6	0,6	-	180	6	1
KITMA8R	8	1 250	8	0,6	-	290	8	1
KITMA10R	6	1 250	10	0,6	-	290	10	1
KITMA5625	-	250 x 625	5	0,6	-	180	-	1