



Steel wire rope sling - type 2

Produktinformation

- 2 legs steel wire rope is equipped with pressing buckles, master ring and a latch hooks
- wire rope strength 1770 N / mm²
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

Märkning: CE-märkning

Säkerhetsfaktor: 5:1

Art.nr	Lindiameter mm	WLL 0°-45° ton	WLL 45-60° t	Ca. levtid (arbetsdagar)
TER20601	6	0,49	0,35	14
TER20801	8	0,98	0,7	14
TER21001	10	1,47	1,05	14
TER21201	12	2,17	1,55	14
TER21401	14	2,968	2,12	14
TER21601	16	3,78	2,7	14
TER21801	18	4,76	3,4	14
TER22002	20	6,09	4,35	14
TER22202	22	7,28	5,2	14
TER22402	24	8,82	6,3	14
TER22602	26	10,08	7,2	14
TER22802	28	11,76	8,4	14
TER23002	30	13,58	9,7	14
TER23202	32	15,4	11	14
TER23603	36	19,6	14	14
TER24003	40	23,8	17	14
TER24403	44	29,4	21	14
TER24803	48	35	25	14
TER25203	52	40,6	29	14
TER25603	56	46,9	33,5	14
TER26003	60	54,6	39	14

Ritning & mått

