



Steel wire rope - type 8

Produktinformation

- The steel wire rope is equipped with pressing buckles, loop end and a latch hook
- wire rope strength 1770 N / mm²
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

Märkning: CE-märkning

Art.nr	Lindiameter mm	Max last (WLL) ton	Eye diameter mm	Ca. levtid (arbetsdagar)
TER80601	6	0,35	100	14
TER80801	8	0,7	150	14
TER81001	10	1,05	150	14
TER81201	12	1,55	200	14
TER81401	14	2,12	200	14
TER81601	16	2,7	250	14
TER81801	18	3,4	250	14
TER82002	20	4,35	300	14
TER82202	22	5,2	300	14
TER82402	24	6,3	350	14
TER82602	26	7,2	350	14
TER82802	28	8,4	400	14
TER83002	30	9,7	400	14
TER83202	32	11	400	14
TER83603	36	14	-	14
TER84003	40	17	-	14
TER84403	44	21	-	14
TER84803	48	25	-	14
TER85203	52	29	-	14
TER85603	56	33,5	-	14
TER86003	60	39	-	14

Ritning & mått

