

Spur Gear Hand Winch TL300-600 Painted

Produktinformation



This convenient spur gear winch excels by its speed. It is equipped with a load-pressure brake with a double ratchet system and a semi-closed housing. In short, a fine, easy winch!

- robust and safe lifting and pulling winch
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards
- adjustable crank
- suitable for wall mounting
- 1 layer of paint

Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- ATEX certified zone 2 and 22 (EX)
CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

... [Read more](#)


Märkning: Enligt standard, CE-märkning

Standard: EN 13157

Säkerhetsfaktor: 4:1

Spur Gear Hand Winch TL300-600 Painted

Ritning & mått



Mer information / Reservdelar

Art.nr	Benämning	Max last (WLL) ton	Lina Ø mm	Rope capacity m	Kapacitet 1:a lagret kg	Capacity top layer kg	Vikt kg
TL300	TL300	0,3	4	35,4	300	172	10
TL600	TL600	0,6	6	12,3	600	336	11