



Worm Gear Hand Winch WW2000-7500 Painted

Produktinformation

This hand winch is very safe due to the natural braking effect of the worm gear transmission in combination with the load pressure brake. In addition, the winch is easy to use, can be mounted in various ways and has a cable storage up to 120 meters.

- winch suitable for lifting and pulling
- load pressure brake with double ratchet system for safe stable hold of the load in any position
- cable outlet upwards or at rear
- adjustable crank
- suitable for wall and (optional) floor mounting
- 1 layer of paint

Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- grooved drum (GD)
- 2 drum compartment (2D) or multiple up to 8 (XD)
- suitable for floor mounting (FM)
- suitable for Dyneema rope (DY)
- pressure roller (PR)
- free-spooling device for pulling applications. To disengage the drum (FS)
- free-spooling device with additional friction brake for controlled cable unwinding (FSB)
- ATEX certified zone 2 and 22 (EX)
 - CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
 - CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

Märkning: Enligt standard, CE-märkning

Standard: EN 13157

Säkerhetsfaktor: 4:1

Art.nr	Benämning	Max last (WLL) ton	WLL Lifting outer layer (kg)	Rope capacity m	Lina Ø mm	Kapacitet 1:a lagret kg	Lyfthastighet m/min	Handkraft max. kg	Amm mm	B mm	C mm	D mm	G, H, J mm	K mm	L mm	M mm	N mm	O mm	P mm	R mm	S mm	Vikt kg	Ca. levtid (arbetsdagar)
WW2000	WW2000	2	1 075	60,5	12	2 000	0,3	15	410	310	196	360	137 177 133	25	312	372	57	705	380	434	220	60	17
WW3000	WW3000	3	1 667	68,7	14	3 000	0,3	14	436	380	251	386	137 203 168	25	375	480	65	813	380	536	220	78	17
WW4000	WW4000	4	2 223	53	14	4 000	0,1	13	436	380	251	386	137 203 168	25	375	480	65	813	380	536	220	80	17
WW5000	WW5000	5	3 276	57,8	16	5 000	0,2	15	436	467	316	386	137 200 219	25	437	515	75	847	380	618	220	117	17
WW7500	WW7500	7,5	3 752	72,6	22	7 500	0,1	15	510	500	350	455	189 202 245	25	630	635	75	968	380	748	220	190	17

Ritning & mått

