

Master Link M GrabiQ

Produktinformation




Märkning: Enligt standard
Standard: EN 1677-4

Säkerhetsfaktor: 5:1
Klass: 10

Master Link M GrabiQ

Ritning & mått



Lyfttabell

Art.nr	Benämning	Max last (WLL) ton	D mm	E mm	L mm	Vikt kg
NORA1006M	M-6-10	1,5	11	60	100	0,2
NORA1086M	M-86-10	2,5	13	60	120	0,4
NORA1008M	M-108-10	4	17	80	140	0,8
NORA1013M	M-13-10	6,8	19	90	150	1
NORA101310M	M-1310-10	7,5	22	95	160	1,5
NORA101613M	M-1613-10	10	28	110	190	2,8
NORA1019M	M-19-10	12	30	120	200	3,5
NORA102016M	M-2016-10	17	34	140	240	5,2
NORA102220M	M-2220-10	25	40	150	250	7,3
NORA102622M	M-2622-10	28	42	150	250	8,7
NORA1032M	M-32-10	33	45	180	340	12,9
NORA103226M	M-3226-10	43	50	200	300	14,8
NORA103632M	M-3632-10	56	55	200	350	20,7
NORA104536M	M-4536-10	70	60	210	375	26,4