



Coupling Link Gunnebo, G Grabiq

Produktinformation

For use with master link and eye hook.

Märkning: Enligt standard

Standard: EN 1677

Säkerhetsfaktor: 4:1

Klass: 10

Art.nr	Benämning	Kätting Ø mm	Max last (WLL) ton	A mm	B,	C,	F,	L	Vikt kg	Ca. levtid (arbetsdagar)
LLA1006G	G-6-10	6	1,5	8	15	16	7	45	0,1	14
LLA1007G	G-7-10	7	2	11	18	22	9	56	0,2	14
LLA1008G	G-8-10	8	2,6	11	18	22	9	56	0,2	14
LLA1010G	G-10-10	10	4	13	25	26	12	68	0,3	14
LLA1013G	G-13-10	13	6,8	17	29	33	15	89	0,7	14
LLA1016G	G-16-10	16	10,3	20	36	40	19	106	1,4	14
LLA1020G	G-20-10	20	16	26	43	44	23	125	2,2	14
LLA1022G	G-22-10	22	20	28	50	59	26	152	3,6	14
LLA1026G	G-26-10	26	27,3	34	58	61	32	161	5,7	14
LLA1032G	G-32-10	32	40	40	70	77	38	200	9,5	14

Ritning & mått

