



## Digital load indicator with remote reading 3-10 t

### Produktinformation

The crane scale/load indicator can be used as a normal crane scale or, for example, to measure pulling forces. Equipped with an illuminated LCD display. Operating time with rechargeable 3×AA NiMH batteries approx. 30 hours. Includes charger.

Wireless remote reader has a range of 50-70 m (unobstructed visibility). The weight of the load is updated in real time on the screen. It displays the battery charge level of remote and the load indicator's battery. Equipped with a rechargeable battery. Supplied with charging cable (USB-C)

Remote reader functions: display backlight, tare, peak, hold, unit change, automatic shutdown, battery charge indicator, signal strength, time/date, password to start.

**Märkning:** CE-märkning

**Säkerhetsfaktor:** 4:1

| Art.nr  | Max last (WLL)<br>ton | Resolution<br>kg | A<br>mm | B mm | C mm | D<br>mm | E<br>mm | F<br>mm | Vikt<br>kg | Ca. levtid (arbetsdagar) |
|---------|-----------------------|------------------|---------|------|------|---------|---------|---------|------------|--------------------------|
| KV3KIE  | 3                     | 1                | 360     | 95   | 91   | 67      | 59      | 50      | 3,4        | 1                        |
| KV5KIE  | 5                     | 2                | 400     | 95   | 91   | 67      | 73      | 53      | 5,6        | 1                        |
| KV10KIE | 10                    | 5                | 560     | 95   | 91   | 67      | 123     | 90      | 13         | 1                        |

