



Winch Pulley-Man

Produktinformation

Lifting or hauling winch. Capacity: 300 kg single line or 600 kg double line. Easy installation and dismantling, compact and light weight at 3.5kg. 12 m supplied working length - this can be increase considerably.

Powered by reverable hand drill or screwdriver. Horizontal/Vertical/Slant working conditions by fixed mainbody or fixed wire hook method. Trouble-free automatic holding - brake function (patented gear-reducer). Can do many jobs in any 360 rotating direction. Supplied with 12 m of galvanized steel rope 4.76 mm, 7x19+WSC. Self-locking gear. Other lengths also available, ask more about our sales.

In the 600 kg model, a winch will be equipped with extra pulley wheel. If you want 600 kg model please select PM300 + PM600 (extra pulley).

Product code explanations:

PM300: Entire winch 300 kg

PM600: Just a pulley that gives the winch a load of WLL 600 kg

TEK47515K: Spare part steel wire 15 m, loop at one end (no hook)

TEK47520K: Spare part steel wire 20 m, loop at one end (no hook)

PM300KOUKKU: Spare part hook, fits the wire and top of the winch

Art.nr	Max last (WLL) ton	Lina Ø mm	Linlängd m	Pulling length m	Lyfthöjd m	Vikt kg	Ca. levtid (arbetsdagar)
PM300	0,3	4,76	12	12	12	3	10
PM600	0,6	4,76	12	6	6	5	1
TEK47515K	-	4,75	15	-	-	-	1
TEK47520K	-	4,75	20	-	-	-	1
PM300KOUKKU	-	-	-	-	-	-	1