

Safety Screw Clamp, Tiger

Produktinformation

The Tiger CSS safety screw cam clamp with double eye anchor points & safety torque feature is suitable for many applications. This screw cam clamp is for all-purpose uses, such as lifting, lateral pulling and turning over materials. Adequacy of tightening can be visually confirmed by the visual torque safety feature.

- Spherical universal designed screw cam provides an extra powerful clamping force on a workpiece even when vibrations occur during operation.
- Cam holder and collar have phosphorescent (glow-in-the dark) paint for easy recognition of adequate torque tightening.
- No tools required – integrated adjusting screw spindle

Certification:

Each unit comes fully certified with a test certificate or an EC Declaration of Conformity stating compliance with the essential health and safety requirements of the Machinery Directive 2006/42/EC.

Märkning: CE-märkning

Säkerhetsfaktor: 4:1



Art.nr	Max last (WLL) ton	Jaw width mm	D1 mm	D2 mm	H mm	H1 mm	H2 mm	L mm	L2 mm	S mm	T1 mm	T2 mm	Vikt kg	Ca. levtid (arbetsdagar)
LTCSS05TI	0,5	0-25	27	27	121	72	30	158	89	17	46	13	1,9	14
LTCSS10TI	1	0-40	32	32	161	94	45	208	121	21	54	14	3,6	14
LTCSS20TI	2	0-40	36	32	177	105	45	227	121	21	60	18	4,8	14
LTCSS32TI	3,2	0-40	45	35	196	119	50	252	136	21	64	20	7	14
LTCSS63TI	6,3	0-50	50	41	225	132	55	291	151	21	90	43	17	14

Ritning & mått

