



## Double Swivel Ring Codipro DSR UP UNC

### Produktinformation

The DSR lifting ring is a double swivel ring. It is composed of a GRADUP lifting ring designed for rotations under load. Its double swivel ensures perfect alignment with the sling. The lifting ring can swivel 180° but has a rotating range of 360°. It can be used for any lifting configuration (straight lift, with angle, tilting, rotating).

The DSR lifting ring is equipped with a protective crossbar and is approved for all lifting configurations from 0° to 90°.

It is manufactured in compliance with the REACH regulation and is also available as female and stainless-steel, quick lift and welding version.

Complies with the Machinery Directive 2006/42/CE

**Märkning:** Enligt standard, CE-märkning

**Standard:** EN 1677-1

*med undantag för klass/WLL (maxlast).*

**Säkerhetsfaktor:** 5:1

Art.nr	Max last (WLL) ton	Thread Inch	A mm	B, C,	D mm	E, F, G,	H,	L1 mm	S1 mm	S2 mm	Vikt kg	Ca. levtid (arbetsdagar)
NS8KL1/4DSR	0,14	1/4 -20	32	30 30	38	27 14 53	9,5	13	8	16	0,3	10
NS8R5/16DSR	0,45	5/16 -18	33	30 30	38	27 14 53	9,5	15	8	16	0,3	10
NS8KL3/8DSR	0,58	3/8 -16	33	30 30	38	27 14 53	9,5	17	8	16	0,3	10
NS8KL1/2DSR	1,08	1/2 -13	33	30 30	38	27 14 53	9,5	21	8	16	0,3	10
NS8KL5/8DSR	1,76	5/8 -11	45	40 45	53	38 17 76	13	27	8	20	0,9	10
NS8KL3/4DSR	2,38	3/4 -10	45	40 45	53	38 17 76	13	30	8	20	0,9	10
NS8KL7/8DSR	3,58	7/8 -9	62	55 60	83	55 25 115	19	33	14	24	2,5	10
NS8KL1DSR	5,08	1 -8	62	55 60	83	55 25 115	19	36	14	24	2,6	10
NS8KL11/8DSR	5,21	1 1/8 -7	62	55 60	83	55 25 115	19	42	14	24	2,6	10
NS8KL11/4DSR	6,12	1 1/4 -7	62	55 60	83	55 25 115	19	45	14	24	2,7	10

# Ritning & mått

