



Electric Chain Hoist LIFTKET STAR ONE 030 125 - 1.000 kg

Produktinformation

Electric Chain Hoist Liftket STAR ONE impresses with its load-dependent speed control. Thanks to its speed ramp, it enables smooth acceleration and deceleration. STAR ONE can be easily connected to any single-phase grid with a voltage of 110 to 240 V and a frequency of 50 or 60 Hz. This wide compatibility enables universal use worldwide, regardless of regional power grid standards. This makes the device ideal for international applications and various locations.

Features:

- Single-phase grid
- Load-dependent lifting speeds
- Power supply 230 V, 1 phase, 50 Hz
- Up to 1.000 kg load capacity
- Standard lifting height 3 m
- 1.5m control cable
- Control pendant with emergency stop
- Protection class IP55
- Equipped with EASY CONNECT
- VFD control 24 V DC
- Upper/lower limit switches
- Starting and slowing down by speed ramp

Märkning: CE-märkning

Art.nr	Benämning	Max last (WLL) ton	Lyfthöjd m	Lifting speed m/min	Antal kättingfall	Motor kW	Klass ISO/FEM	Lyftkätting mm	A	B, C, G, H,	I	J, K	M	N	O	P	V	Vikt kg	Ca. levtid (arbetsdagar)	
SKT125KV1S1	125/1-8	0,125	3	8	1	0.70/0.00	M4/ 1Am	5.2x15	221	235220365525	15	20	19	12	37	40	24	74	22	35
SKT250KV1S1	250/1-8	0,25	3	7	1	0.70/0.00	M4/ 1Am	5.2x15	221	235220365525	15	20	19	12	37	40	24	74	22	35
SKT500KV1S1	500/1-8	0,5	3	5	1	0.70/0.00	M4/ 1Am	5.2x15	221	235220365525	15	20	19	12	37	40	24	74	22	35
SKT1000KV2S1	1000/2-4	1	3	2,5	2	0.70/0.00	M4/ 1Am	5.2x15	221	235220428540	19	22	24	12	37	40	24	74	26	35

Ritning & mått

