



## Lashing system 50 mm / LC 2500 daN / loading dock

### Produktinformation

The Haklift loading dock lashing system ensures that trailers are securely fastened to the loading dock during loading and unloading. The product is an essential part of modern logistics and occupational safety solutions, as it minimizes vehicle movement and prevents damage and personal injury during loading and unloading.

#### Construction

- The length of the ratchet part is 1.0 m and it is equipped with a shackle (SAK47PBP)
- The length of the webbing end is 3.0 m and it is equipped with a single-wire triangular hook

#### Intended use

The loading dock lashing system is attached between the trailer and the loading dock attachment points, keeping the trailer securely attached to the dock throughout the loading or unloading operation. This prevents:

- Unintentional movement of the trailer, which can occur, for example, as a result of forklift movements or weight transfer of the load.
- Premature detachment of the trailer from the dock.
- Impact and damage caused by gaps between the loading equipment and the vehicle.

#### The importance of occupational safety

The use of a loading lashing system is recommended because:

- It improves personnel safety by reducing unexpected vehicle/trailer movements.
- It prevents dangerous situations during loading and unloading, such as forklift overturning or load slippage.
- It supports practices that require effective securing and locking methods before loading or unloading operations begin.

#### Features and benefits

- The tie-down strap ensures reliable fastening between the trailer and the loading dock, keeping the vehicle in place even under the dynamic forces caused by load transfer.
- Easy and quick to use: Designed for professional use, enabling quick attachment and removal without tools.
- Increased work safety: Reduces the risk of accidents and helps to fulfill the company's work safety obligations.
- Compatibility: Suitable for various trailers and platforms, and can be used as a stand-alone solution or as part of a larger loading dock fastening system.

**Who it is suitable for**

The Haklift loading dock strap is intended for logistics and manufacturing companies, warehouses, transport companies, and other operators who need a reliable and professional solution for securing trailers during loading and unloading.

| <b>Art.nr</b> | <b>Benämning</b> | <b>LC<br/>daN</b> | <b>Min. brottlast<br/>ton<br/>ton</b> | <b>Bandbredd<br/>mm</b> | <b>Längd<br/>m</b> | <b>Vikt<br/>kg</b> | <b>Ca. levtid (arbetsdagar)</b> |
|---------------|------------------|-------------------|---------------------------------------|-------------------------|--------------------|--------------------|---------------------------------|
| SV3500042SAKO | SV3500042SAKO    | 2 500             | 5                                     | 50                      | 3 + 1              | 2,4                | 7                               |